



CABLECOMM ENGINEERING PTE. LTD.

10 Jalan Besar #02-10 Sim Lim Tower Singapore 208787.

Tel: 6291 6566

Fax: 6291 1887

Company Reg. NO.: 201218346Z

GST Reg NO.: 201218346Z

Standalone Access Controller Reader

Stainless Steel Body

Card + Password

Door Bell Support

- Full programming from the keypad
- 2000 users, supports Card, PIN, Card+PIN
- Can be used as a stand alone keypad
- Backlight keys
- Wiegand 26 input for connection to external reader
- Wiegand 26 output for connection to a controller
- Very low power consumption (30mA)
- Fast operating speed, <20ms with 2000 users
- Lock output current short circuit protection
- Easy to install and program
- Built in light dependent resistor (LDR) for anti tamper
- Built in buzzer
- Red, Yellow and Green LEDS display the working status



Model Number	AC-T4EM
Dimensions	56(L) x 20(W) x 120(H) mm
Capacity	2000 users
Reading Range	3 ~ 6 cm
Active Current	<60mA
Idle Current	25±5 mA
Lock Output Load	Max 3A
Alarm Output Load	Max 20A
Operating Temperature	-45°C ~ 60°C
Operating Humidity	10%-90%RH
Adjustable Door Relay Time	0-99 seconds
Adjustable Alarm Time	0-3 minutes
Wiegand Interface	Wiegand 26 bits
Wiring Connections	Electric Lock, Exit Button, External Alarm